

Hard drawn wire mesh @485MPA					Strength ladder	Ductile Plus 500E mesh				
WIRE DIAMETER	SPACING	CROSS SECTION	KN/M WIDTH	MESHES	KN/METRE WIDTH	WIRE DIAMETER	SPACING	CROSS SECTION	KN/METRE WIDTH	MESHES
					175					
					170					
					165					
					160	9.0	200	318.1	159.0	SE92
					155					
					150					
7.5	150.0	294.5	142.8	661	140					
					135					
					130					
7.1	150.0	263.9	128.0	662*	125	8.0	200	251.3	125.7	SE82
					120					
					110	9.0	300	212.1	106.0	SE93
9.0	300.0	212.1	102.8	212	100					
6.3	150.0	207.8	100.8	663	95	7.0	200	192.4	96.2	SE72
					90					
6.0	150.0	188.5	91.4	664*	85					
7.5	235.0	188.0	91.2	188*	80					
					75	7.5	300	147.3	73.6	SE73
5.3	150.0	147.1	71.3	665	70	6.1	200	146.1	73.1	SE62
7.5	235.0	147.3	71.4	147	60					
5.3	50.0	441.2	214.0	225	55					
4.0	150.0	83.8	40.6	668	50					
5.6	300.0	82.1	39.8	84	40					

* Denotes mesh no longer available ex-stock / made to order only